

# DuraSCOPE™

## MICRON CAMERA REELS

Proudly Designed and Manufactured in North America



Micron Reel for use with VividHD Command Modules



Micron Wi-Fi Reel for use with phone or tablet



## Upgrade to DuraSCOPE™!

Micron DuraSCOPE™ camera reels can be used with any Hathorn control module or used with your own mobile Apple/Android device, if you choose the Wi-Fi PipeSTREAM™ stream/record option. The Wi-Fi option is a standalone camera system that allows live streaming and recording to up to four devices at the same time.

DuraSCOPE™ Micron reels are trusted by plumbers, general contractors, and home inspectors to deliver high definition, recordable video inspections. These municipal grade reels offer butt-welded steel frame construction and premium 1/4" cable allowing you to push further in a small diameter pipe. Hathorn DuraSCOPE™ reels come equipped with your choice of DuraCAM™ 1" or 7/8" straight view camera heads, allowing you to inspect pipes from 1" to 4" with ease. DuraCAM™ heads are also equipped with super bright, cool running LEDs for optimal HD picture quality.

Micron reels are only 16" tall and weigh under 16 lbs. The Wi-Fi option is powered by an external Milwaukee™ 18V or compatible battery, which can last up to 6 hours. These features give Micron reels the ultimate in portability and allow you to stay in the field longer.



# HATHORN

North America: 1-866-HATHORN  
International: +1-905-604-7040

[www.hathorncorp.com](http://www.hathorncorp.com) • [info@hathorncorp.com](mailto:info@hathorncorp.com)

# DuraSCOPE™

## MICRON CAMERA REELS



Micron Camera Reel used with an M18 Command Module.



### WI-FI OPTION SPECIFICATIONS

- Compatibility – Wi-Fi PipeSTREAM™ stream/record (App for Apple or Android)
- Power – 18V Milwaukee™ battery or equivalent or included AC/DC adapter
- Camera Heads - DuraCAM™ straight view camera heads with HD picture quality and auto-iris technology
- Non-Dimmable Lighting – 8 super bright cool running LEDs for long camera life ~8,000 LUX at 6"
- Push Rod – with premium 1/4" rod with HDPE jacket
- Sonde - 512 Hz High-power sonde
- Operating Temperature – -30C to 60C (-22F to 140F)
- Ingress Protection of Reel & Camera Head – IPx5 to 60PSI

### NON-WI-FI OPTION SPECIFICATIONS


- Compatibility – All Hathorn M10, M12 & M18 controllers
- Power – Powered using Hathorn control module
- Camera Heads - DuraCAM™ straight view camera heads with HD picture quality and auto-iris technology
- Dimmable Lighting – 8 super bright cool running LEDs for long camera life ~8,000 LUX at 6"
- Push Rod – with premium 1/4" rod with HDPE jacket
- Sonde - 512 Hz High-power sonde
- Operating Temperature – -30C to 60C (-22F to 140F)
- Ingress Protection of Reel & Camera Head – IPx5 to 60PSI

	Catalog #	Wi-Fi	Camera Head	Self Leveling	Rod Length	Rod Size	Min 90° Elbow	Max. Pipe Well Lit	LBS.	Dimensions
Micron	MC-1100	No	1"	No	100ft.	1/4"	1.5"	4"	15lbs	16"x12"x10"
	MC-1078	No	7/8"	No	100ft.	1/4"	1.5"	4"		
	WMC-1100	Yes	1"	No	100ft.	1/4"	1.5"	4"	16lbs	
	WMC-1078	Yes	7/8"	No	100ft.	1/4"	1.5"	4"		

\* Camera head skirts are included and always recommended to protect camera heads. Find these accessories and spare parts at our website - [www.hathorncorp.com](http://www.hathorncorp.com)



Wi-Fi App available at:



# HATHORN

North America: 1-866-HATHORN  
International: +1-905-604-7040

[www.hathorncorp.com](http://www.hathorncorp.com) • [info@hathorncorp.com](mailto:info@hathorncorp.com)